

The substrate uses a brilliant white textured vinyl wallcovering with a non-woven backing. It is suitable for a whole range of applications, from an personalized mural for consumers or a tailor made and decorative wallcovering for hotels, offices or (healthcare) institutions, to a durable shop interior or creative set design. The textured coated surface ensures a striking and vibrant color range.

Technical Datasheet

Vinyl 350

Composition:

Total Weight
Weight Non woven
Weight coating 1)

: 350 ± 20
: 60 ± 20
: 290 ± 20

Dimensions

gsm.
gsm.
gsm.

Test method

ISO 2286-2

1) Coating

: Specially formulated acrylic laquer with exclusive inkjet properties

Thickness

: Depends on embossing / structure

Printing inks

Suitable for

: Latex, Eco-solvent - Solvent - UV-curable

Resistance to chemicals prior to printing

Resistant to
Not resistant to

: Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.
: Solvents like Ketones; Esters; Aromatic hydrocarbons

Washability prior to printing

: Extra washable

EN 259-1 / EN 12956

Lightfastness:

: 7 out of 8 International Woolscale BS EN 20105 / ISO 105-B02

Adhesives

: Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute

Safety/Ecological

: The material is classified as non-hazardous

DIN 52900 or 91/155/EEG,2001/58/EC

Fire resistance

: Euro class - B s1-d0
B1 - ABP nr - P-MPA-E-04-507

Specifications

- Vibrant colors
- Weight: 350g/m²
- Thickness: 0.50 mm
- Printed with ink (Green guard certificate, low chemical emissions)
- UV-resistant
- Fire Classification Bs1-d0 (European) & ASTM 84 (American)
- Width: 50 cm (19,68 inch) & 100 cm (39,37 inch)
- Dry-removable: comes off easily.
- Textured finish
- 100% Anti-Microbial (treated with biocide)
- Contract material
- Super washable
- Scratch resistant

